

The Multi-Color Engravable Polymer Sheet

King ColorCore is a versatile, environmentally stabilized sheet with multiple layers of contrasting colors. Its thin cap layers and bright primary colors make it ideal for signage, marine, playground and recreational applications. For maximum versatility, standard colors are made to coordinate with King ColorBoard. King ColorCore is easy to engrave and machine, as the cap is approximately .050" thick. King ColorCore is made with high-impact-resistant polymer to handle more abuse than conventional sign materials. It will not warp, rot or delaminate. King ColorCore is a superior homogeneous sheet, made with a unique state-of-the-art continuous process called Polyfusion, manufactured to the highest standards in the industry. Base materials are FDA approved.

King ColorCore is upgradable to King MicroShield[®] with an exclusive antimicrobial additive from Biosafe[®], the latest technology for protecting the product surface against stain and odor causing bacteria, algae and fungi.*

King ColorCore is upgradable with King FlameShield for ASTM E-84 Class A or B Flame Compliance and CAN/ULC-S102 for Canadian Compliance.

For more information about King MicroShield and King FlameShield, please visit www.kingplastic.com

Engraving Products







Applications

- Architectural Applications
- Carnival Games
- Children's Furniture
- Furniture
- Marine Applications
- Museums
- Picnic Tables
- Point-of-Purchase Displays
- Signage and Wayfinding

Specifications		Standard Colors		
Standard Sheet Size in: 48" x 96" mm: 1219mm x 2438mm	Blue/White/Blue	White/Blue/White	Red/White/Red	White/Red/White
Standard Gauges in: 1/4" 1/2" 3/4" mm: 6.4mm 12.7mm 19mm	Red/Black/Red	Black/Red/Black	Green/White/Green	White/Green/White
Approximate Weight Ibs: 40 lbs 80 lbs 120 lbs kg: 18kg 36kg 54kg	Green/Tan/Green	Tan/Green/Tan	Yellow/Black/Yellow	Black/Yellow/Black
Cap thickness is .050" for both sides of the material Tolerance information: Gauges 1/4" up to 3/4" ± 5% Length and width plus only at room temperature Custom sheet sizes, gauges, and colors available	Brown/Tan/Brown Black/White/Black	Tan/Brown/Tan	Brown/White/Brown Note: Color accuracy con computer monitors consult your distributor sample before making Disclaimer: King Micro color. King FlameShield	s and printers. Please or for a product critical color choices. Shield® may affect

Active ingredient (Biosafe®).....antimicrobial siloxane EPA Reg. No. 83019-1

*For bacteriostatic, fungistatic, & algistatic properties. This product is exempt from registration under 40 CFR 152.25(a). King MicroShield® effectiveness verified by ISO and ASTM standards. This product does not protect users or others from disease-causing bacteria. Always clean this product thoroughly after use. Biosafe® is a registered trademark of BIOSAFE, Inc.: Patent number 7,851,653 and 7,858,141.

Properties	Units	ASTM	Nominal Values
Density	g/cc	D1505	0.955
Tensile Strength @ Yield	psi	D638	>4,100
Tensile Modulus	psi	D638	255,000
Elongation @ Yield	%	D638	9.8
Elongation @ Break	%	D638	>600
Flexural Modulus	psi	D790	185,000
Flexural Stress @ 5% Strain	psi	D790	3,810
Compressive Properties 10% Strain	psi	D695	4,950
Durometer	Shore D	D2240	68
Tensile Impact	ft.lbs./in.2	D1822	115
Izod Impact Resistance	ft.lbs./in.2	D256	1.1
Brittleness Temp.	°C (°F)	D746	<-76°C (<-105°F)
Vicat Softening	°C (°F)	D1525	123°C (253°F)
Heat Deflection Temp. 66 psi	°C (°F)	D648	75°C (167°F)
Screw and Nail Withdrawal	lbs	D1761	657 & 63
Flammability	Rating	UL94	HB

All values are determined on specimens prepared according to ASTM Standards. Nominal values should not be interpreted as specifications.

King ColorCore[®] is made entirely from FDA and made with USDA approved materials.

King ColorCore® meets ASTM D4976. The raw material used to make King ColorCore® does not contain BPA's or Phthlates.



1100 N. Toledo Blade Blvd. | North Port, FL 34288 USA **P:** 941.493.5502 | **F:** 941.497.3274 | www.kingplastic.com

and color.